

**Panasonic**



35





  
VARICAM

35

  
4K  
PROFESSIONAL

# Create Emotion

## The VariCam® 35 — Changing the Way Emotion is Created

The VariCam line of cameras has been used on a wide variety of movies, commercials, and TV programs, and is renowned for its color reproduction, look, and for bringing progressive workflows to the production industry.

Now the VariCam 35 has arrived. Drawing on the traditions of the original VariCam line, VariCam 35 helps its users create emotion with its amazing latitude, wide color gamut, and 4K resolution. It also revolutionizes workflow with the addition of dual-codec recording, in-camera color grading, and a modular design.

The feature-rich VariCam 35 is ready to create emotion for your next project.



# Film-like Images at 4K Resolution, and Revolutionary New VariCam Workflows



## 4K Images with the VariCam Look

- Newly developed super35mm sensor ideal for 4K (4096 x 2160) and UHD (3840 x 2160) shooting.
- Wide dynamic range 14+ stops of latitude.
- Dual native ISO at ISO 800 and 5000 keeping S/N and dynamic range.
- V-Gamut: wide color gamut.
- V-Log: tuned for emotional images.
- V-709: cinematic tuned Rec 709.
- Built-in ND filters (0.6ND, 1.2ND, 1.8ND, CLEAR).
- Built-in low-pass filter tuned for 4K and UV/IR-cut filter.

## Revolutionary Dailies in Camera


- **In-camera Color Grading**  
Color grading function (CDL/3D LUT) allows on-set color grading using control panel or 3rd party software\*. CDL/3D LUT files is recorded together with clip.
- **Double Recorder**  
Records ungraded 4K master with grading information and graded HD images simultaneously.
- **Dual Codec Recording**  
Simultaneously records in two different formats, codecs and selectable from V-Log/V-709/Grading.

## Multiple Codec, Multiple Outputs

- Supports AVC-Intra4K for 4K and UHD recording.
- Supports AVC-Intra2K for 2K recording.\*1
- AVC-Intra100, AVC-Intra200\*1 and Apple ProRes\*1\*2 for HD recording.
- Records 24 bit/48 kHz sampling, four channel high-quality digital audio and metadata.
- Variable frame rate recording in the range of 1 fps to 120 fps.\*3
- Allows cable-less docking of a Codex V-RAW Recorder.\*1\*4
- Provided with 3G-SDI 4K QUAD (BNC x 4) output, Monitor output x 3 and AUDIO (XLR x 2) input.



\*1: To be supported by firmware upgrade. For details, please visit Panasonic website. (<http://pro-av.panasonic.net/>) \*2: ProRes is licensed from Apple Inc. The ProRes codec component is licensed from ATOMOS. \*3: 120fps recording is to be supported by firmware upgrade. \*4: Codex V-RAW Recorder is the product of Codex. The use of DCF Technologies is under license from Multi-Format, Inc.



Large-diameter EVF



Detachable control panel



Installation of control panel



Flat top body and handle with screw holes

## Newly Developed EVF and Control Panel

### EVF (AU-VCVF1G)

- High-resolution 0.7 type (1280 x 720 pixels) OLED panel shows a wide field angle with viewfinder magnification of 0.78x.
- Large-diameter 38 mm eyepiece lens offer comfortable viewing with minimum vignetting.
- Optical zoom and advanced focus assist function.

### Control Panel (on AU-VREC1G)

- Detachable control panel for enhanced camera flexibility.
- 3.5 type LCD display panel for live preview.
- Direct access to frequently used menu.

## Modularity

- Modular structure with independent camera head and recorder module. Dockable camera head is interchangeable with the VariCam HS.
- Flat top and bottom panels for easy installation of various plates.
- Mounting holes provided on both sides and handle for convenient mounting of accessories.
- Shoulder mount module (AU-VSHL1G) can be moved in a range of 110 mm in the front and back direction to accommodate a diversity of lenses.



## Durability and Reliability

- The lens mount section is made of stainless steel, and designed to prevent flange back deviation due to temperature changes.
- Body made of strong and rigid aluminum alloy.
- Cooling system designed for effective dissipation of heat from the circuitry section.


# VARICAM 35 WORKFLOW\*1

## In Camera Color Grading

Remote operation by control panel or 3rd party software\*3



# VARICAM 35 MODULAR SYSTEM



**AU-V35C1G**  
4K Camera Module



**AU-V23HS1G**  
2/3 type HD Camera Module



**AU-VREC1G**  
Recording Module



**AU-VCVF1G**  
Electronic HD Color View Finder



**AU-VSHL1G**  
Shoulder Mount Module



**AJ-WM30G**  
Wireless Module\*3



**AU-XP0256AG**  
Memory Card "expressP2 card" (256 GB model)



**AU-XPD1**  
Memory Card Drive "expressP2 drive"

\*1: This chart shows an example of the workflow using VariCam 35. \*2: Codex V-RAW Recorder is a product of Codex. This will be available in the near future and supported by VariCam 35 by firmware upgrade. For details, please visit Panasonic website (<http://pro-av.panasonic.net/>).

\*3: To be supported by firmware upgrade. For details, please visit Panasonic website. (<http://pro-av.panasonic.net/>)

## General (Combination of AU-V35C1G and AU-VREC1G)

Power:	DC 12 V (11.0 V – 17.0 V)
Power Consumption:	69 W (Body only) 99 W (With all optional accessories connected and maximum power supplied from each output terminal)
Operating Temperature:	0°C to 40°C
Operating Humidity:	10% to 85% (Relative humidity)
Storage Temperature:	-20°C to 60°C
Weight:	Approx. 5.0 kg (Body only)
Dimensions (W x H x D) :	179 mm x 230.5 mm x 347 mm (7-1/16 inches x 9-1/16 inches x 13 -21/32 inches) (Body only, excluding protrusion)

## Camera Module (AU-V35C1G)

Pickup Device:	super35 mm MOS 8.9 million pixels
Lens Mount:	35 mm PL mount
Optical Filter:	ND filter: 1: CLEAR, 2: 0.6 ND 3: 1.2 ND, 4: 1.8 ND
Gain Settings:	[ISO] mode: ISO 800 to 12800 [dB] mode: 0 to 24 dB (3 dB step)
Shutter speed:	[deg] mode: 1.0 to 358 deg (0.5 deg step) [sec] mode: 1/24 to 1/250 (When 24p mode)

## Recording Module (AU-VREC1G) When used with AU-V35C1G Memory Card Recorder

Recording Media:	expressP2 card, P2 card, microP2 card
Recording Resolution:	4096 x 2160, 3840 x 2160, 1920 x 1080
Recording Framerate:	Maximum 4K/UHD 50p/60p, HD 50p/60p
System Frequency:	59.94p, 50p, 29.97p, 25p, 23.98p
Recording Format:	Main Recorder: AVC-Intra4K 4:2:2, AVC-Intra100 Sub Recorder: AVC-Intra100, AVC-LongG50, AVC-LongG25
Recording Video Signal:	4096 x 2160/59.94p, 50p, 29.97p, 25p, 23.98p 3840 x 2160/59.94p, 50p, 29.97p, 25p, 23.98p 1920 x 1080/59.94p, 50p, 29.97p, 25p, 23.98p
Recording Time: (Main Codec)	(When expressP2 card 256 GB is used)*2 Approx. 90 min. (AVC-Intra4K 4:2:2, VFR OFF, 23.98p) Approx. 36 min. (AVC-Intra4K 4:2:2, VFR ON, 50fps/60fps) Approx. 128 min. (AVC-Intra 100, VFR ON, 50fps/60fps)
Recording Time: (Sub Codec)	(When microP2 card 64 GB is used)*2 Approx. 64 min. (AVC-Intra100, 25p/29.97p) Approx. 128 min. (AVC-LongG50, 25p/29.97p) Approx. 256 min. (AVC-LongG25, 25p/29.97p)

## Digital Video

Quantizing:	10 bit
Video Compression Format:	AVC-Intra4K 4:2:2/AVC-Intra100: MPEG-4 AVC/H.264 Intra Profile AVC-LongG50/AVC-LongG25: MPEG-4 AVC/H.264

## Digital Audio

Recording Audio Signal:	48 kHz/24 bit, 4 ch Head room 18 dB/20 dB menu switchable
-------------------------	--

## Proxy

File Format:	MOV
Video Compression Format:	H.264/AVC High Profile
Audio Compression Format:	LPCM
Recording Time (1 GB)*2:	Approx. 25 min.

## Video Input/Output

SDI OUT:	HD (1.5G)/3G-SDI, 0.8 V[p-p], 75 Ω (1 set, 4 pieces)
MON OUT1:	HD (1.5G)/3G-SDI, 0.8 V[p-p], 75 Ω
MON OUT2:	HD (1.5G)/3G-SDI, 0.8 V[p-p], 75 Ω
VF SDI:	HD (1.5G)/3G-SDI, 0.8 V[p-p], 75 Ω

## Audio Input/Output

AUDIO IN (CH1/CH2):	XLR x 2, 3 pin, LINE/MIC/MIC+48 V/AES switchable
MIC IN:	XLR x 1, 5 pin
PHONES:	Stereo mini jack
Speaker:	20 mm diameter, round x 1

## Other Input/Output

GENLOCK IN:	HD (1.5G)/3G-SDI, 0.8 V[p-p], 75 Ω
TC IN/OUT:	BNCx1, IN/OUT switch selection IN: 0.5 V[p-p] to 8 V[p-p], 10 kΩ OUT: 2.0 ± 0.5 V[p-p], Low impedance
DC IN:	XLR 4 pin, DC 12 V (DC 11.0 V to 17.0 V)
DC OUT/RS:	4 pin, DC 12 V (DC 11.0 V to 17.0 V), maximum output current 1.0 A
DC OUT:	2 pin, DC12 V (DC 11.0 V to 17.0 V), maximum output current 1.0 A
LENS:	12 pin x 1, 4 pin x 2
VF:	14 pin
LAN:	100BASE-TX/10BASE-T
USB2.0 (device) :	Type B connector, 4 pin
USB2.0 (host) :	Type A connector, 4 pin *3
EXT:	50 pin (for external recording only) *3

## Control Panel

Display Panel:	LCD, 3.5-type QHD color monitor Approx. 1.56 million dots
----------------	--

## Electronic HD Color View Finder (AU-VCVF1G)

Display Panel:	OLED, 0.7-type, Approx. 2.76 million dots
Signal Input:	1080/59.94p, 1080/50p

\*1: Specification is preliminary as of October 2014. Specification subject to change upon firmware upgrade. For the latest specification, please visit Panasonic website. (<http://pro-av.panasonic.net/>) \*2: These are reference values for continuous recording. The recording time may differ depending on the scene or the number of clips \*3: This will be supported by firmware upgrade. For details, please visit Panasonic website. (<http://pro-av.panasonic.net/>)

# Panasonic®

**Panasonic Corporation**  
**AVC Networks Company**  
 2-15 Matsuba-cho, Kadoma, Osaka 571-8503  
 Japan  
<http://pro-av.panasonic.net/>

Facebook: <https://www.facebook.com/Varicam>  
 Twitter: <https://twitter.com/theVaricam>



**[Countries and Regions]**

Argentina +54 11 4122 7200  
 Australia +61 (0) 2 9491 7400  
 Bahrain +973 252292  
 Brazil +55 11 3889 4035  
 Canada +1 905 624 5010  
 China +86 10 6515 8828  
 Hong Kong +852 2313 0889  
 Czech Republic: +421 (0) 903 447 757  
 Denmark +45 43 20 08 57  
 Egypt +20 2 23938151  
 Finland, Latvia, Lithuania, Estonia +358 (9) 521 52 53  
 +33 (0) 1 47 91 64 00  
 France  
 Germany, Austria, Switzerland +49 (0) 6103 313887  
 Greece +30 210 96 92 300  
 Hungary +36 (1) 382 60 60  
 India +91 1860 425 1860  
 Indonesia ++65 6277 7284  
 Iran (Vida) +98 21 2271463  
 (Panasonic Office)+98 2188791102

Italy +39 02 6788 367  
 Jordan +962 6 5859801  
 Kazakhstan +7 727 298 0891  
 Korea +82 2 2106 6641  
 Kuwait +96 522431385  
 Lebanon +96 11665557  
 Malaysia +60 3 7809 7888  
 Mexico +52 55 5488 1000  
 Netherlands, Belgium +31 73 640 2729  
 New Zealand +64 9 272 0100  
 Norway +47 67 91 78 00  
 Pakistan +92 5370320 (SNT)  
 Palestine +972 2 2988750  
 Panama +507 229 2955  
 Philippines +65 6277 7284  
 Poland +48 (22) 338 1100  
 Portugal +351 21 425 77 04  
 Romania, Albania, Bulgaria, Macedonia +40 (0) 729 164 387  
 Russia & CIS +7 495 9804206  
 Saudi Arabia +96 626444072

Singapore +65 6277 7284  
 Slovak Republic, Croatia, Serbia, Bosnia, Montenegro, Slovenia +421 (0) 903 447 757  
 South Africa +27 11 3131622  
 Spain +34 (93) 425 93 00  
 Sweden +46 (8) 680 26 41  
 Syria +963 11 2318422/4  
 Taiwan +886 2 2227 6214  
 Thailand +662 731 8888  
 Turkey +90 216 578 3700  
 U.A.E. (for All Middle East) +971 4 8862142  
 +380 44 4903437  
 Ukraine +44(0)1344 70 69 13  
 U.K.  
 U.S.A. +1 877 803 8492  
 Vietnam +65 6277 7284



JQA-0443



Factories of AVC Networks Company have received ISO14001:2004-the Environmental Management System certification. (Except for 3rd party's peripherals.)